



- A P-Metric light truck/SUV tire with all-season, all-terrain applications.
  - Computerized tread pattern created for optimal performance on all road surfaces and in all seasons.
  - Tread design created for optimal handling and a quiet, comfortable ride.
  - Robust footprint shape ensures even pressure distribution, precise handling, even treadwear and long life.
- Un pneu P-métrique pour camionnettes et VUS avec applications toutes saisons, tous terrains.
  - Dessin informatisé de la bande de roulement créé pour une performance optimale sur toutes surfaces en toutes saisons.
  - Dessin de la sculpture conçu pour un comportement optimal avec une portée confortable et silencieuse.
  - Robuste empreinte qui assure une distribution égale de la pression, un comportement précis, une usure régulière et une longue vie.

# DynaproAT

## RF08 Sizes & Specifications/Grandeurs et Caractéristiques

UTQG/Classe UTQG: 460/A/B

IN	Size	PR	SW	Code	Price \$	MR/RWR	Max Air (psi)	Max Load (kgs)	Max Load (lbs)	Overall Diameter Inch	Section Width Inch	Tread Depth Inch/32"	
Po	Dimensions	Plis	Flanc	Code	Prix \$	JM/LJ	Pression Max. (li/po²)	Charge Max. (kg)	Charge Max. (lb)	Diamètre Total po	Largeur Section po	Épais. Bande Roul. po/32"	
15	P215/75R15	100S	4	OWL 1003070		6.0	-	44	790	1742	27.6	8.5	12.3
	P225/70R15	100S	4	OWL 1003071		6.5	-	44	795	1753	27.3	8.9	12.4
	P225/75R15	102S	4	OWL 1003073		6.0	-	44	850	1874	28.2	8.7	12.4
	P235/70R15	102S	4	OWL 1003075		7.0	-	44	860	1896	27.9	9.4	12.5
	P235/75R15	105S	4	OWL 1003077		6.5	-	44	920	2028	28.8	9.2	12.5
	P235/75R15 XL	108S	4	OWL 1003078		6.5	-	50	990	2183	28.8	9.2	12.5
	P265/70R15	110S	4	OWL 1003463		8.0	-	44	1060	2337	29.5	10.7	12.9
	P265/75R15	112S	4	OWL 1003083		7.5	-	44	1120	2469	30.6	10.6	12.9
16	P225/70R16	101S	4	OWL 1003072		6.5	-	44	825	1819	28.4	8.9	12.4
	P225/75R16	104S	4	OWL 1003074		6.0	-	44	900	1984	29.3	8.7	12.4
	P235/70R16	106S	4	OWL 1003076		7.0	-	44	950	2094	28.9	9.4	12.5
	P245/70R16	106S	4	OWL 1003079		7.0	-	44	950	2094	29.4	9.8	12.6
	P245/75R16	109S	4	OWL 1003080		7.0	-	44	1030	2271	30.4	9.7	12.6
	P255/65R16	106S	4	OWL 1004071		7.5	-	44	950	2094	29	10.1	12.5
	P255/70R16	109S	4	OWL 1003081		7.5	-	44	1030	2271	30	10.2	12.8
	P265/70R16	112S	4	OWL 1003190		8.0	-	44	1120	2469	30.5	10.7	12.9
	P265/75R16	114S	4	OWL 1003084		7.5	-	44	1180	2601	31.6	10.6	12.6
	17	P235/65R17	103S	4	OWL 1003955		7.0	-	44	875	1929	29.2	9.4
P235/75R17		108S	4	OBL 1002438		6.5	6.5-8.0	35	1,000	2,205	30.9	9.4	13.0
P255/60R17		105S	4	OWL 1003957		7.5	-	44	925	2039	29.2	10.1	12.5
P255/70R17		110S	4	OWL 1004073		7.5	-	44	1060	2337	31.2	10.3	12.8
P265/70R17		113S	4	OWL 1003082		8.0	-	44	1150	2535	31.8	10.7	12.9
P275/60R17		110S	4	OWL 1003958		8.0	-	44	1060	2337	30.1	10.9	12.8