



MICHELIN[®] LTX[®] M/S

This tire will make your journey to adventure a pleasure with its great performance in mud and snow and an exceptionally comfortable, quiet highway ride. A special casing design provides comfort while the unique tread block pattern minimizes road noise.

Benefits

Extra all-season control



Extra long tread life

Michelin® LTX® M/S

UTQG RATING: P Metric

Treadwear	Traction	Temperature
440	A	B
520	Except P275/70R16 114H	
	A	A

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Static Loaded Radius	Rev./Mile	Tread Depth (in/32nds)	SINGLE MAX LOAD (LBS.) PER AXLE @ PSI	DUAL MAX LOAD (LBS.) PER AXLE @ PSI
P205/75R15	97S	ORWL	70051	5.5 - 7.5	8.1 on 6.0	27.0	12.1	777	13	2,905 @ 35	-
P215/75R15	100S	ORWL	23526	5.5 - 7.5	8.6 on 5.5	27.6	12.4	754	13	3,167 @ 35	-
P225/75R15	102S	ORWL	76017	6.0 - 8.0	9.0 on 6.5	28.3	12.7	741	13	3,407 @ 35	-
P235/75R15	105S	ORWL	26632	6.0 - 8.5	9.4 on 7.0	28.7	13.0	728	13	3,687 @ 35	-
P235/75R15 XL	108S	ORWL	29394	6.0 - 8.5	9.4 on 7.0	28.8	12.9	728	13	3,969 @ 41	-
P235/75R15 XL	108S	ORBL	57653	6.0 - 8.5	9.4 on 7.0	28.8	12.9	728	13	3,969 @ 41	-
P225/70R15	100S	ORWL	48079	6.0 - 8.0	9.0 on 6.0	27.4	12.3	765	13	3,187 @ 35	-
P235/70R15	102S	ORWL	97679	6.0 - 8.0	9.4 on 7.0	27.9	12.6	746	13	3,448 @ 35	-
P235/75R16	106S	ORWL	76374	6.0 - 8.0	9.4 on 6.5	29.9		696	13	1,904 @ 35	-
P245/75R16	109S	ORWL	63571	6.5 - 8.0	9.7 on 7.0	30.4	13.5	684	13	4,130 @ 35	-
P265/75R16	114S	ORWL	97979	7.0 - 9.0	10.5 on 7.5	31.6	14.0	658	13	4,730 @ 35	-
P215/70R16	99S	ORWL	60041	5.5 - 7.0	8.7 on 6.5	27.8	12.6	755	13	3,107 @ 35	-
P225/70R16	101S	ORWL	52470	6.0 - 7.0	8.9 on 6.5	28.4	12.9	738	13	3,308 @ 35	-
P225/70R16	101S	ORBL	62260	6.0 - 7.0	8.9 on 6.5	28.4	12.9	738	13	3,308 @ 35	-
P235/70R16	104S	ORWL	59257	6.0 - 7.5	9.6 on 7.0	29.1	13.1	722	13	3,607 @ 35	-
P245/70R16	106S	ORWL	84843	6.5 - 8.0	9.8 on 7.0	29.6	13.3	703	13	3,808 @ 35	-
P255/70R16	109S	ORWL	39992	6.5 - 8.0	10.3 on 7.5	30.2	13.5	694	13	4,130 @ 35	-
P265/70R16	111S	ORWL	85423	7.0 - 8.5	10.7 on 8.0	30.7	13.8	681	13	4,370 @ 35	-
P275/70R16	114S	ORBL	43428	7.0 - 10.0	11.1 on 8.0	31.3	13.7	666	12	4,729 @ 44	-
P275/70R16 ¹	114H	ORBL	98835	7.0 - 10.0	11.1 on 7.5	31.3	13.7	666	12	4,729 @ 44	-
P255/65R16	106S	ORBL	61571	7.0 - 9.0	10.1 on 7.5	29.2	13.0	712	11	3,807 @ 35	-
P265/70R17	113S	ORWL	66259	7.0 - 8.5	10.8 on 8.0	31.8	14.3	656	13	4,611 @ 35	-
P245/65R17	105S	ORBL	62573	7.0 - 8.5	9.6 on 7.0	29.7	13.3	700	11	3,708 @ 35	-
30X9.50R15	LRC	ORWL	09418	6.5 - 8.5	9.6 on 6.5	29.6	13.7	706	15	3,970 @ 50	-
31X10.50R15	LRC	ORWL	24798	7.0 - 9.0	11.1 on 7.0	30.8	14.2	679	15	4,540 @ 50	-
32X11.50R15	LRC	ORWL	09478	8.0 - 10.0	11.6 on 8.0	31.7	14.7	662	15	5,070 @ 50	-
T195/75R14	LRC	ORWL	10674	5.5 - 6.0	7.7 on 5.0	25.5	11.8	824	13	2,870 @ 50	5,300 @ 50
T215/75R15	LRC	ORWL	26820	5.5 - 7.0	8.5 on 5.5	27.7	12.8	755	13	3,530 @ 50	6,440 @ 50
T235/75R15	LRC	ORWL	78868	6.0 - 7.0	9.3 on 6.0	28.8	13.0	727	13	3,970 @ 50	7,280 @ 50
T215/85R16	LRD	ORBL	20898	5.5 - 7.5	8.5 on 5.5	30.5	14.1	685	15	4,670 @ 65	8,600 @ 65
T215/85R16	LRE	ORBL	57810	5.5 - 7.0	8.7 on 6.0	30.5	14.1	685	15	5,360 @ 80	9,880 @ 80
T235/85R16	LRD	ORBL	06854	6.0 - 7.0	9.0 on 6.0	31.9	14.8	655	15	5,246 @ 65	9,524 @ 65
T235/85R16	LRE	ORBL	07364	6.0 - 7.0	9.2 on 6.0	32.0	14.8	655	15	6,084 @ 80	11,112 @ 80
T235/85R16	LRE	ORWL	16658	6.0 - 7.0	9.2 on 6.0	32.0	14.8	655	15	6,084 @ 80	11,112 @ 80
T225/75R16	LRD	ORBL	00978	6.0 - 7.0	9.3 on 6.5	29.3	13.6	709	15	4,670 @ 65	8,600 @ 65
T225/75R16	LRD	ORWL	20436	6.0 - 7.0	9.3 on 6.5	29.3	13.6	709	15	4,670 @ 65	8,600 @ 65
T225/75R16	LRE	ORBL	25516	6.0 - 7.0	8.8 on 6.5	29.4	13.6	709	15	5,360 @ 80	9,880 @ 80
T225/75R16	LRE	ORWL	65141	6.0 - 7.0	8.8 on 6.0	29.4	13.6	709	15	5,360 @ 80	9,880 @ 80
T245/75R16	LRE	ORBL	22606	6.5 - 7.0	9.9 on 6.5	30.7	14.2	681	15	6,084 @ 80	11,112 @ 80
T245/75R16	LRE	ORWL	60856	6.5 - 7.0	9.9 on 6.5	30.7	14.2	681	15	6,084 @ 80	11,112 @ 80
T265/75R16	LRC	ORWL	10570	7.0 - 8.0	10.5 on 7.0	31.8	14.7	658	15	4,940 @ 50	9,080 @ 50
T265/75R16	LRE	ORWL	52169	7.0 - 8.0	10.7 on 7.5	31.8	14.7	652	14	6,830 @ 80	12,340 @ 80
T285/75R16	LRD	ORWL	78276	7.5 - 9.0	11.3 on 8.0	32.8		634	15	6,000 @ 65	-

Michelin® tires and tubes are subject to a continuous development program. Michelin North America (Canada), Inc. reserves the right to change product specifications at any time without notice or obligation.

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.

2. Overall width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

Note: Use only on rims designated by the rim manufacturer as suitable for radial tires. Passenger sizes in Light Truck applications have reduced load. This will differ from maximum load molded on tire sidewall.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

WARNING: Serious or fatal injury may result from: • Tire failure due to under-inflation/over-inflation/over-loading – follow owner's manual or Tire Information Placard in vehicle. • Explosion of tire/rim assembly due to improper mounting – never inflate beyond 40 psi to seat beads. See Tire Dealer for proper mounting. • Mixing bias tires with radials on the same vehicle. • Mixing different tire sizes – follow vehicle manufacturer's recommendations.

Longer tire life because of large contact patch and enhanced tread block stability.

Exceptionally quiet ride due to the noise-minimizing tread block pattern.

Increased durability because of a third steel belt in D & E load ranges.

Longer tread life thanks to state-of-the-art casing that more evenly distributes stresses.

Exceptional wet traction results from deep, circumferential grooves.

Excellent snow traction and enhanced cornering due to interlocking, full-depth sipes and tread block stability.

Maintain excellent grip in all weather conditions because of special tread rubber compound.

Attractive, sporty look with bold, new sidewall styling.

