



# MICHELIN<sup>®</sup> PILOT<sup>®</sup> SPORT PS2

Superior handling and grip both wet and dry conditions.

## **Benefits**

Precision handling and control in high speed cornering



Extreme predictability in wet and dry max handling



Reduced road noise

# Michelin® Pilot® Sport PS2

## UTQG RATING:

| Treadwear | Traction | Temperature |
|-----------|----------|-------------|
| 220       | AA       | A           |

| Size                 | Load Index, Speed Symbol | Sidewall | Product Code | Rim Width Range (inches) | Section Width on Recommended Rim (inches) | Overall Diameter (inches) | Revs/Mile | Tread Depth (32nds) | Max Load (lbs @ psi) |
|----------------------|--------------------------|----------|--------------|--------------------------|---|---------------------------|-----------|---------------------|----------------------|
| 225/45Z17            | 91Y                      | RRBL     | 89192        | 7.0 - 8.5                | 8.9 on 7.5                                | 25.0                      | 833       | 10.0                | 1,356 @ 51           |
| 225/45Z17 "MO"       | 91Y                      | RRBL     | 81556        | 7.0 - 8.5                | 8.9 on 7.5                                | 25.0                      | 833       | 10.0                | 1,356 @ 51           |
| 235/40Z17            | 90Y                      | RRBL     | 65519        | 8.0 - 9.5                | 9.5 on 8.5                                | 24.4                      | 852       | 10.0                | 1,323 @ 51           |
| 245/40Z17 "MO"       | 91Y                      | RRBL     | 92706        | 8.0 - 9.5                | 9.8 on 8.5                                | 24.7                      | 841       | 10.0                | 1,356 @ 51           |
| 245/40Z17            | 91Y                      | RRBL     | 82268        | 8.0 - 9.5                | 9.8 on 8.5                                | 24.7                      | 841       | 10.0                | 1,356 @ 51           |
| 225/40Z18 REINF      | 92Y                      | RRBL     | 93617        | 7.5 - 9.0                | 9.2 on 8.0                                | 25.1                      | 829       | 10.0                | 1,389 @ 50           |
| 235/40Z18 "N2"       | 91Y                      | RRBL     | 95853        | 8.0 - 9.5                | 9.5 on 8.5                                | 25.4                      | 819       | 9.5                 | 1,356 @ 51           |
| 235/40Z18 REINF      | 95Y                      | RRBL     | 79659        | 8.0 - 9.5                | 9.5 on 8.5                                | 25.4                      | 819       | 10.0                | 1,521 @ 50           |
| 245/40Z18            | 93Y                      | RRBL     | 76261        | 8.0 - 9.5                | 9.8 on 8.5                                | 25.7                      | 809       | 10.0                | 1,433 @ 51           |
| 245/40Z18            | 93Y                      | RRBL     | 78337        | 8.0 - 9.5                | 9.8 on 8.5                                | 25.7                      | 809       | 10.0                | 1,433 @ 51           |
| 225/35Z18 REINF      | 87Y                      | RRBL     | 87255        | 7.5 - 9.0                | 9.1 on 8.0                                | 24.2                      | 859       | 10.0                | 1,201 @ 50           |
| 255/35Z18 REINF      | 94Y                      | RRBL     | 45327        | 8.5 - 10.0               | 9.7 on 8.5                                | 25.2                      | 827       | 10.0                | 1,477 @ 50           |
| 265/35Z18 REINF      | 97Y                      | RRBL     | 74289        | 9.0 - 10.5               | 10.7 on 9.5                               | 25.3                      | 822       | 10.0                | 1,609 @ 50           |
| 265/35Z18 REINF "MO" | 97Y                      | RRBL     | 45290        | 9.0 - 10.5               | 10.7 on 9.5                               | 25.3                      | 822       | 10.0                | 1,433 @ 50           |
| 275/35Z18            | 95Y                      | RRBL     | 85356        | 9.0 - 11.0               | 10.9 on 9.5                               | 25.6                      | 814       | 10.0                | 1,521 @ 51           |
| 295/35Z18            | 99Y                      | RRBL     | 43008        | 10.0 - 11.5              | 11.9 on 10.5                              | 26.1                      | 797       | 9.5                 | 1,709 @ 51           |
| 295/30Z18 REINF "N2" | 98Y                      | RRBL     | 49127        | 10.0 - 11.0              | 11.9 on 10.5                              | 25.0                      | 832       | 9.5                 | 1,653 @ 50           |
| 315/30Z18 "N2"       | 98Y                      | RRBL     | 96031        | 10.5 - 11.5              | 12.6 on 11.0                              | 25.5                      | 817       | 10.0                | 1,653 @ 51           |
| 225/40Z19 REINF      | 93Y                      | RRBL     | 93395        | 7.5 - 9.0                | 9.1 on 8.0                                | 26.1                      | 797       | 9.5                 | 1,433 @ 50           |
| 245/40Z19 REINF      | 98Y                      | RRBL     | 68396        | 8.0 - 9.5                | 9.8 on 8.5                                | 26.7                      | 778       | 9.5                 | 1,653 @ 50           |
| 225/35Z19 REINF      | 88Y                      | RRBL     | 93379        | 7.5 - 9.0                | 9.1 on 8.0                                | 25.2                      | 824       | 10.0                | 1,235 @ 50           |
| 235/35Z19 REINF      | 91Y                      | RRBL     | 88492        | 8.0 - 9.5                | 9.5 on 8.5                                | 25.5                      | 817       | 10.0                | 1,356 @ 50           |
| 245/35Z19 REINF      | 93Y                      | RRBL     | 78831        | 8.0 - 9.5                | 9.8 on 8.5                                | 25.8                      | 807       | 10.0                | 1,433 @ 50           |
| 255/35Z19 REINF      | 96Y                      | RRBL     | 74098        | 8.5 - 10.0               | 10.2 on 9.0                               | 26.0                      | 799       | 9.5                 | 1,565 @ 50           |
| 265/35Z19 "NO"       | 94Y                      | RRBL     | 69837        | 9.0 - 10.5               | 10.7 on 9.5                               | 26.3                      | 790       | 9.5                 | 1,477 @ 51           |
| 275/35Z19 REINF      | 100Y                     | RRBL     | 48468        | 9.0 - 11.0               | 10.9 on 9.5                               | 26.6                      | 783       | 10.0                | 1,764 @ 50           |
| 265/30Z19 REINF      | 93Y                      | RRBL     | 50536        | 9.0 - 10.0               | 10.7 on 9.5                               | 25.3                      | 822       | 10.0                | 1,433 @ 50           |
| 275/30Z19 REINF      | 96Y                      | RRBL     | 81049        | 9.0 - 10.0               | 10.9 on 9.5                               | 25.6                      | 814       | 10.0                | 1,565 @ 50           |
| 285/30Z19 REINF      | 98Y                      | RRBL     | 41439        | 9.5 - 10.5               | 11.4 on 10.0                              | 25.8                      | 807       | 10.0                | 1,653 @ 50           |
| 295/30Z19 REINF      | 100Y                     | RRBL     | 89005        | 10.0 - 11.0              | 11.9 on 10.5                              | 26.0                      | 799       | 10.0                | 1,764 @ 50           |
| 315/25Z19 REINF      | 98Y                      | RRBL     | 89776        | 11.0 - 12.0              | 12.8 on 11.5                              | 25.2                      | 824       | 9.5                 | 1,653 @ 50           |
| 245/35Z20 REINF      | 95Y                      | RRBL     | 52728        | 8.0 - 9.5                | 9.8 on 8.5                                | 26.8                      | 777       | 10.0                | 1,521 @ 50           |
| 255/35Z20 REINF      | 97Y                      | RRBL     | 51832        | 8.5 - 10.0               | 10.2 on 9.0                               | 27.1                      | 767       | 10.0                | 1,609 @ 50           |
| 255/30Z20 REINF      | 92Y                      | RRBL     | 93488        | 8.5 - 9.5                | 10.2 on 9.0                               | 26.1                      | 798       | 10.0                | 1,389 @ 50           |
| 285/30Z20 REINF      | 99Y                      | RRBL     | 5985         | 9.5 - 10.5               | 11.0 on 10.0                              | 26.9                      | 774       | 10.0                | 1,709 @ 50           |
| 335/30Z20 "NO"       | 104Y                     | RRBL     | 81438        | 11.5 - 12.5              | 13.5 on 12.0                              | 28.0                      | 744       | 9.5                 | 1,984 @ 51           |
| 295/25Z20 REINF      | 95Y                      | RRBL     | 52046        | 10.0 - 11.0              | 11.9 on 10.5                              | 25.8                      | 805       | 10.0                | 1,521 @ 51           |
| 245/35Z21 REINF      | 96Y                      | RRBL     | 74422        | 8.0 - 9.5                | 9.8 on 8.5                                | 27.8                      | 749       | 10.0                | 1,565 @ 50           |
| 285/30Z21 REINF      | 100Y                     | RRBL     | 87692        | 9.5 - 10.5               | 11.4 on 10.0                              | 27.8                      | 749       | 10.0                | 1,764 @ 50           |
| 295/25Z22 REINF      | 97Y                      | RRBL     | 83945        | 10.0 - 11.0              | 11.9 on 10.5                              | 27.8                      | 747       | 10.0                | 1,609 @ 50           |

RRBL= Recessed Raised Black Letters

NO, N2 = Developed for Porsche  
MO = Developed for Mercedes

Michelin® tires and tubes are subject to a continuous development program. Michelin North America (Canada) Inc. reserves the right to change product specifications at any time without notice or obligation.

- The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
- Section width varies by approximately 0.2" (5 mm) for every 0.5" change in rim width.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

WARNING: Serious or fatal injury may result from improper mounting, from underinflation/overinflation/overloading or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper tire size and inflation pressure, consult Tire Information Placard in vehicle. For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h, load and inflation (psi) must be adjusted according to the table below.

| Y-rated sizes:           | 160 | 170 | 180 | 190 | 200 | 210 |
|--------------------------|-----|-----|-----|-----|-----|-----|
| MAXIMUM SPEED (km/h)     | 160 | 170 | 180 | 190 | 200 | 210 |
| INFLATION INCREASE (psi) | 0   | 1   | 2   | 3   | 4   | 5   |
| LOAD CAPACITY (% of max) | 100 | 100 | 100 | 100 | 100 | 100 |

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a consumer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended or endorsed. Sizes and preliminary data subject to change.

IMPORTANT: While All-Season tires are designed to provide reliable performance in some winter conditions, the use of four winter tires is recommended for optimal winter performance.