



# MICHELIN<sup>®</sup> PILOT<sup>®</sup> SPORT PS2

Superior handling and grip both wet and dry conditions.

## **Benefits**

Precision handling and control in high speed cornering



Extreme predictability in wet and dry max handling



Reduced road noise

# Michelin® Pilot® Sport PS2

## UTQG RATING:

Treadwear	Traction	Temperature
220	AA	A

Size	Load Index, Speed Symbol	Sidewall	Product Code	Rim Width Range (inches)	Section Width on Recommended Rim (inches)	Overall Diameter (inches)	Revs/Mile	Tread Depth (32nds)	Max Load (lbs @ psi)
225/45ZR17	91Y	RRBL	89192	7.0 - 8.5	8.9 on 7.5	25.0	833	10.0	1,356 @ 51
225/45ZR17 "MO"	91Y	RRBL	81556	7.0 - 8.5	8.9 on 7.5	25.0	833	10.0	1,356 @ 51
235/40ZR17	90Y	RRBL	65519	8.0 - 9.5	9.5 on 8.5	24.4	852	10.0	1,323 @ 51
245/40ZR17 "MO"	91Y	RRBL	92706	8.0 - 9.5	9.8 on 8.5	24.7	841	10.0	1,356 @ 51
245/40ZR17	91Y	RRBL	82268	8.0 - 9.5	9.8 on 8.5	24.7	841	10.0	1,356 @ 51
225/40ZR18 REINF	92Y	RRBL	93617	7.5 - 9.0	9.2 on 8.0	25.1	829	10.0	1,389 @ 50
235/40ZR18 "N2"	91Y	RRBL	95853	8.0 - 9.5	9.5 on 8.5	25.4	819	9.5	1,356 @ 51
235/40ZR18 REINF	95Y	RRBL	79659	8.0 - 9.5	9.5 on 8.5	25.4	819	10.0	1,521 @ 50
245/40ZR18	93Y	RRBL	76261	8.0 - 9.5	9.8 on 8.5	25.7	809	10.0	1,433 @ 51
245/40ZR18	93Y	RRBL	78337	8.0 - 9.5	9.8 on 8.5	25.7	809	10.0	1,433 @ 51
225/35ZR18 REINF	87Y	RRBL	87255	7.5 - 9.0	9.1 on 8.0	24.2	859	10.0	1,201 @ 50
255/35ZR18 REINF	94Y	RRBL	45327	8.5 - 10.0	9.7 on 8.5	25.2	827	10.0	1,477 @ 50
265/35ZR18 REINF	97Y	RRBL	74289	9.0 - 10.5	10.7 on 9.5	25.3	822	10.0	1,609 @ 50
265/35ZR18 REINF "MO"	97Y	RRBL	45290	9.0 - 10.5	10.7 on 9.5	25.3	822	10.0	1,433 @ 50
275/35ZR18	95Y	RRBL	85356	9.0 - 11.0	10.9 on 9.5	25.6	814	10.0	1,521 @ 51
295/35ZR18	99Y	RRBL	43008	10.0 - 11.5	11.9 on 10.5	26.1	797	9.5	1,709 @ 51
295/30ZR18 REINF "N2"	98Y	RRBL	49127	10.0 - 11.0	11.9 on 10.5	25.0	832	9.5	1,653 @ 50
315/30ZR18 "N2"	98Y	RRBL	96031	10.5 - 11.5	12.6 on 11.0	25.5	817	10.0	1,653 @ 51
225/40ZR19 REINF	93Y	RRBL	93395	7.5 - 9.0	9.1 on 8.0	26.1	797	9.5	1,433 @ 50
245/40ZR19 REINF	98Y	RRBL	68396	8.0 - 9.5	9.8 on 8.5	26.7	778	9.5	1,653 @ 50
225/35ZR19 REINF	88Y	RRBL	93379	7.5 - 9.0	9.1 on 8.0	25.2	824	10.0	1,235 @ 50
235/35ZR19 REINF	91Y	RRBL	88492	8.0 - 9.5	9.5 on 8.5	25.5	817	10.0	1,356 @ 50
245/35ZR19 REINF	93Y	RRBL	78831	8.0 - 9.5	9.8 on 8.5	25.8	807	10.0	1,433 @ 50
255/35ZR19 REINF	96Y	RRBL	74098	8.5 - 10.0	10.2 on 9.0	26.0	799	9.5	1,565 @ 50
265/35ZR19 "NO"	94Y	RRBL	69837	9.0 - 10.5	10.7 on 9.5	26.3	790	9.5	1,477 @ 51
275/35ZR19 REINF	100Y	RRBL	48468	9.0 - 11.0	10.9 on 9.5	26.6	783	10.0	1,764 @ 50
265/30ZR19 REINF	93Y	RRBL	50536	9.0 - 10.0	10.7 on 9.5	25.3	822	10.0	1,433 @ 50
275/30ZR19 REINF	96Y	RRBL	81049	9.0 - 10.0	10.9 on 9.5	25.6	814	10.0	1,565 @ 50
285/30ZR19 REINF	98Y	RRBL	41439	9.5 - 10.5	11.4 on 10.0	25.8	807	10.0	1,653 @ 50
295/30ZR19 REINF	100Y	RRBL	89005	10.0 - 11.0	11.9 on 10.5	26.0	799	10.0	1,764 @ 50
315/25ZR19 REINF	98Y	RRBL	89776	11.0 - 12.0	12.8 on 11.5	25.2	824	9.5	1,653 @ 50
245/35ZR20 REINF	95Y	RRBL	52728	8.0 - 9.5	9.8 on 8.5	26.8	777	10.0	1,521 @ 50
255/35ZR20 REINF	97Y	RRBL	51832	8.5 - 10.0	10.2 on 9.0	27.1	767	10.0	1,609 @ 50
255/30ZR20 REINF	92Y	RRBL	93488	8.5 - 9.5	10.2 on 9.0	26.1	798	10.0	1,389 @ 50
285/30ZR20 REINF	99Y	RRBL	5985	9.5 - 10.5	11.0 on 10.0	26.9	774	10.0	1,709 @ 50
335/30ZR20 "NO"	104Y	RRBL	81438	11.5 - 12.5	13.5 on 12.0	28.0	744	9.5	1,984 @ 51
295/25ZR20 REINF	95Y	RRBL	52046	10.0 - 11.0	11.9 on 10.5	25.8	805	10.0	1,521 @ 51
245/35ZR21 REINF	96Y	RRBL	74422	8.0 - 9.5	9.8 on 8.5	27.8	749	10.0	1,565 @ 50
285/30ZR21 REINF	100Y	RRBL	87692	9.5 - 10.5	11.4 on 10.0	27.8	749	10.0	1,764 @ 50
295/25ZR22 REINF	97Y	RRBL	83945	10.0 - 11.0	11.9 on 10.5	27.8	747	10.0	1,609 @ 50

RRBL= Recessed Raised Black Letters

NO, N2 = Developed for Porsche  
MO = Developed for Mercedes

Michelin® tires and tubes are subject to a continuous development program. Michelin North America (Canada) Inc. reserves the right to change product specifications at any time without notice or obligation.

- The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
- Section width varies by approximately 0.2" (5 mm) for every 0.5" change in rim width.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

WARNING: Serious or fatal injury may result from improper mounting, from underinflation/overinflation/overloading or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper tire size and inflation pressure, consult Tire Information Placard in vehicle. For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h, load and inflation (psi) must be adjusted according to the table below.

Y-rated sizes:	160	170	180	190	200	210
MAXIMUM SPEED (km/h)	160	170	180	190	200	210
INFLATION INCREASE (psi)	0	1	2	3	4	5
LOAD CAPACITY (% of max)	100	100	100	100	100	100

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a consumer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended or endorsed. Sizes and preliminary data subject to change.

IMPORTANT: While All-Season tires are designed to provide reliable performance in some winter conditions, the use of four winter tires is recommended for optimal winter performance.